

Technical Data

Antifouling Classic

DESCRIPTION	The self-polishing Plastimo Classic antifouling is particularly suited for sail- and power boats (<40 knots), except aluminium. This product is suitable in moderate fouling areas and for drying berths. Can be applied over standard antifouling paints.				
PRODUCT SPECIFICATIONS	Number of components: 1 Colour : Red, blue, navy blue, black VOC (theoretical): 455 g/l. Volume solid: 54 % ± 2 Flash point: Over 39°C				
SURFACE PREPARATION	1 - GELCOAT OR WOOD Clean the surface with a circular motion with a clean absorbent cloth soaked with Plastimo Epoxy Thinner. Turn cloth over and repeat treatment on the same surface. Change cloth every 2 or 3m ² . Use wet sanding paper (280 for gelcoat and from 180 to 280 for wood) and sand lightly. On a wooden hull, remove dust with a hard brush. Rinse with fresh water and allow to dry. Using a primer from the Plastimo range will ensure better adherence (Epoxy primer for gelcoat and marine plywood and Underwater primer for bare wood). 2 -SURFACES COVERED WITH POOR CONDITION ANTIFOULING Scrape off paint as much as possible. Remove any loose paint with a scraper and a hard brush while washing off with high-pressured water. Rinse off with fresh water and allow to dry. Apply one coat of Underwater primer to improve base. 3 –MAINTENANCE Slightly sand down the old antifouling, rinse off with fresh water and allow to dry.				
PAINT PREPARATION	Mix product thoroughly with a large and flat tool before applying it to homogenise it. If several pots are used, mix them together before application.				
INSTRUCTIONS FOR USE	Application : Brush, roller. The surface must be clean, smooth, dry and must first have been rinsed in fresh water. Thinner: Plastimo Antifouling Thinner Dilution: 5% maximum Film thickness: Damp: 93 microns (per coat) Dry : 50 microns (per coat) Number of coats: 2 Minimum temperature: +5°C Theoretical coverage: 10.8 m ² /litre				
DRYING TIME		10°C	15°C	20°C	35°C
	Interval between coats:	4hrs30	3hrs30	2hrs30	1h30
	Before launching (do not exceed 6 months):	6hrs	5hrs	4hrs	3h
PACKAGING AND STORAGE	Packaging: 0.75L, 2.5L and 5L Storage: 12 months in closed packaging and stored in a sheltered place away from direct sunlight at a temperature ranging from +5°C to +35°C.				
SAFETY DATA	Flammable – Harmful by inhalation, in contact with skin and if swallowed - Irritating to skin - May cause sensitisation by skin contact - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment - Keep out of the reach of children - Use only in well-ventilated areas - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) - Wear suitable protective clothing and gloves – Do not empty into drains, dispose of this material and its container at hazardous or special wast collection point.				