

Technical Data

Underwater Primer

PRESENTATION	The Plastimo Underwater Primer is specially recommended for use as a barrier coat or to improve adhesion on an old and poor condition surface. It is also an excellent primer for wood. The use of a primer is not essential but improves adherence.				
PRODUCT SPECIFICATIONS	Number of components: 1 Colour : Silver VOC (theoretical) : 572 g/l Volume solid: 40% ± 2 Flashing point: Over 34°C				
SURFACE PREPARATION	Remove any loose paint,sand down any imperfections, rinse with fresh water and allow to dry.				
PAINT PREPARATION	Mix product thoroughly with a large and flat tool before application to homogenise it. If several pots are used, mix them together before application.				
INSTRUCTIONS FOR USE	Application : Brush, roller or spray gun (pressure: 15-18 MPa, Tip n°: Graco 721, 723). The surface must be clean, smooth, dry and must first have been rinsed in fresh water. For use on new or bare wood, first coat should be thinned at 5% maximum with Plastimo Antifouling Thinner and apply with brush. Thinner: Plastimo Antifouling Thinner Dilution: Paintbrush and roller: do not dilute Spray gun: 5% maxi. Film thickness: Damp: 100 microns (per coat) Dry : 40 microns (per coat) Number of coats: 1 to 4 Minimum temperature: +5°C Theoretical coverage: 7.2m ² /litre				
DRYING TIME		5°C	10°C	20°C	30°C
	Interval between coats:	12h00	10h00	6h00	5h00
PACKAGING AND STORAGE	Packaging: 0.75L and 2.5L. Storage : 12 months in closed packaging and stored in a sheltered place at a temperature ranging from +5°C to +35°C.				
SAFETY DATA	Flammable – Harmful by inhalation and in contact with skin - Irritating to skin - May cause sensitisation by skin contact - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment - Keep out of the reach of children - Use only in well-ventilated areas - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) - Wear suitable protective clothing and gloves - Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.				